

**WRENCHING WITH
PROVEN TECHNOLOGY.**



ROWRENCH 30.82HKS E³ - 8329900102
 Travelling gear - 5010820006
 Outrigger - 8003082012
 Extension - 5018950005

For tightening and loosening nuts and sleeper, hook and fishplate bolts.

THE ADVANTAGES. YOUR BENEFITS.

Reliable Wrenching, precise results

- Uniform repeat wrenching due to adjustable torque
- Checking of torque on pressure gauge display
- Selection between two gears depending on stiffness of screw
- Fast changeover to maximum torque without changing the torque setting
- Approx. 1000 wrenching cycles per charge of 2300 Wh battery (depending on type of track, condition of track, torque required etc.)

Robust construction, minimum maintenance costs

- Long service life due to ROBEL high-performance clutch
- Low wear due to permanent oil lubrication of clutch in oil bath

Pleasant working for the operator

- Low weight and compact design with folding guide handles
- Large field of view due to LED lighting of work area
- Height-adjustable guide handles
- Very fast availability (at the push of a button)
- No exhaust fumes
- Reduced noise emissions
- Reduced hand-arm vibrations

Flexible use

- Work possible without outrigger due to low centre of gravity
- Tensioning and loosening of all wrenched types of track
- Quick-change chuck for fast change of sockets

SPECIFICATION

Drive	BLDC electric motor
Output	4,0 kW at 3600 rpm
Spindle speed	
No-load speed, max.	200 rpm
Load speed	71 rpm
Adjustable tightening torque	from 140 to 300 Nm
Short loosening torque	up to 1000 Nm
Travelling gear	Transverse bogies available for all gauges Monorail trolleys with outrigger available for all gauges
Dimensions (L x W x H)	1920 x 600 x 600-800 mm
Transport position (L x W x H)	1510 x 600 x 575 mm
Weight machine	from 84 kg (without 2300 Wh battery)
Weight 2300 Wh battery	16 kg

For further information on configuration and accessoires see 30.82HKS Universal Power Wrench.