

Availability of power independent of power supply.

THE ADVANTAGES. YOUR BENEFITS.

- Tested for safety (GS test mark) as per Art. 21
- Meets requirements of VDE Electrical Engineering Association
- Noise emission complies with EEC Directive 84/536 on Noise Protection
- Isolation monitoring with shutdown as per Regulation GW 308 Product Safety Act
- Long operating times due to large tank



ROPOWER 70.01 – 9002100186
Single-axle trolley – 9000600369

SPECIFICATION

Drive	4-stroke petrol engine	4-stroke petrol engine
Type	Honda GX 270, with oil level monitoring	HondaGX 390, with oil level monitoring
Output	5.4 kW	7.5 kW
Output	4 kVA/400 V and 3.7 kVA/230 V, 50 Hz	6.1 kVA/400 V and 5.2 kVA/230 V, 50 Hz
Protection type	IP 54 (protection insulated)	IP 54 (protection insulated)
Weight	from 88 kg	from 100 kg

SPECIFICATION

Drive	4-stroke petrol engine	Diesel engine	Stroke petrol engine
Type	Briggs&Stratton, with oil level monitoring	HATZ 1B50, with oil level monitoring	Yamaha MZ80
Output	12.1 kW at 3600 rpm	7.6 kW at 3000 rpm	1.8 kW
Output	9.0 kVA/400 V and 6.0 kVA/230 V, 50 Hz	6.4 kVA/400 V and 4.5 kVA/230 V, 50 Hz	16 kVA / 230 V, 50 Hz
Protection type	IP 54 (protection insulated)	IP 54 (protection insulated)	IP 23
Weight	from 134 kg	from 132 kg	from 21.5 kg

ACCESSORIES

- 9000600369 Single-axle trolley for transporting the generator, with suspension eyes and rubber handles, with 2 running wheels of 350 mm diameter
- 9008060025 Socket distributor with emergency off switch
- 9008120218 Cable drum/extension lead 30 m long
- 9008230097 Socket transition from Euro socket CEE16A230V to Schuko socket

